

AS/NZS IEC 60331.3:2017
IEC 60331-3:2009

AS/NZS IEC 60331.3:2017

Australian/New Zealand Standard™

**Tests for electric cables under fire
conditions—Circuit integrity**

**Part 3: Test method for fire with shock
at a temperature of at least 830 °C for
cables of rated voltage up to and
including 0.6/1.0 kV tested in a metal
enclosure**



AS/NZS IEC 60331.3:2017

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee EL-003, Electric Wires and Cables. It was approved on behalf of the Council of Standards Australia on 5 March 2017 and by the New Zealand Standards Approval Board on 4 April 2017.

This Standard was published on 1 May 2017.

The following are represented on Committee EL-003:

Australian Cable Makers' Association
Australian Industry Group
Electrical Compliance Testing Association
Electrical Contractors Association of New Zealand
Electrical Regulatory Authorities Council
Institute of Electrical Inspectors
National Electrical and Communications Association
Queensland University of Technology
Worksafe New Zealand

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at www.saiglobal.com or Standards New Zealand web site at www.standards.govt.nz and looking up the relevant Standard in the on-line catalogue.

For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of Standards Australia or the New Zealand Standards Executive at the address shown on the back cover.

AS/NZS IEC 60331.3:2017

Australian/New Zealand Standard™

Tests for electric cables under fire conditions—Circuit integrity

Part 3: Test method for fire with shock at a temperature of at least 830 °C for cables of rated voltage up to and including 0.6/1.0 kV tested in a metal enclosure

Originated as part of AS/NZS 1660.5.5:1998.

Previous edition AS/NZS 1660.5.5:2005.

Jointly revised in part and redesignated as AS/NZS IEC 60331.3:2017.

COPYRIGHT

© Standards Australia Limited

© The Crown in right of New Zealand, administered by the New Zealand Standards Executive

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Australia) or the Copyright Act 1994 (New Zealand).

Jointly published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001 and by Standards New Zealand, PO Box 1473, Wellington 6140.

ISBN 978 1 76035 739 9

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee, EL-003 Electric Wires and Cables, to supersede, in part, AS/NZS 1660.5.5:2005, *Test methods for electric cables, cords and conductors*, Method 5.5: *Fire tests—Circuit integrity*.

The objective of this Standard is to specify the test apparatus and procedure and give the performance requirements, including recommended flame application times, for low-voltage power cables of rated voltage up to and including 0.6/1.0 kV, and control cables with a rated voltage which are required to maintain circuit integrity when tested in a metal enclosure and when subject to fire and mechanical shock under specified conditions.

This Standard is identical with, and has been reproduced from IEC 60331-3, Ed 1.0 (2009), *Tests for electric cables under fire conditions—Circuit integrity*, Part 3: *Test method for fire with shock at a temperature of at least 830 °C for cables of rated voltage up to and including 0,6/1,0 kV tested in a metal enclosure*.

As this Standard is reproduced from an International Standard, the following applies:

- (a) In the source text ‘this part of 60331’ should read ‘this Australian/New Zealand Standard’.
- (b) A full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

CONTENTS

1	Scope	7
2	Normative references.....	7
3	Terms and definitions	7
4	Test conditions – Test environment.....	8
5	Test apparatus	8
5.1	Test equipment.....	8
5.2	Metal enclosure	13
5.2.1	Material and dimensions	13
5.2.2	Metal enclosure selection.....	13
5.3	Test ladder and mounting	13
5.4	Source of heat	14
5.4.1	Burner	14
5.4.2	Flow meters and flow rates	15
5.4.3	Verification	16
5.5	Shock producing device	16
5.6	Positioning of source of heat.....	17
5.7	Continuity checking arrangements	17
5.8	Fuses	17
6	Test specimen	17
6.1	Test specimen preparation.....	17
6.2	Test specimen mounting	18
7	Test procedure	18
7.1	Test equipment and arrangement.....	18
7.2	Electrical connections	18
7.3	Flame and shock application.....	20
7.4	Electrification.....	20
8	Performance requirement	21
8.1	Flame application time	21
8.2	Acceptance criteria	21
9	Retest procedure	21
10	Test report.....	21
	Annex A (normative) Verification procedure for the source of heat	22
	Annex B (informative) Guidance on the choice of recommended test apparatus	24
	Bibliography	25
	Figure 1 – Schematic diagram of test configuration.....	9
	Figure 2 – Recommended method of mounting the metal enclosure to the test ladder	10
	Figure 3 – Plan view of fire test equipment	11
	Figure 4 – End elevation of fire test equipment (not to scale)	12
	Figure 5 – Typical rubber bush for supporting the test ladder	14
	Figure 6 – Burner face	15

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- Looking for additional Standards? Visit Intertek Inform Infostore
 - Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation
-