

Australian Standard™

Composite structures

Part 1: Simply supported beams

This Australian Standard was prepared by Committee BD-032, Composite Construction. It was approved on behalf of the Council of Standards Australia on 3 June 2003 and published on 18 August 2003.

The following are represented on Committee BD-032:

Association of Consulting Engineers Australia

Australian Building Codes Board

Australian Steel Institute

Bureau of Steel Manufacturers of Australia

Institution of Engineers Australia

Steel Reinforcement Institute of Australia

University of New South Wales

University of Adelaide

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Australia web site at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Global Standard*, has a full listing of revisions and amendments published each month.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.com.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

Australian Standard™

Composite structures

Part 1: Simply supported beams

Originated as AS 1480 Supplement 1—1974.
Previous edition AS 2327.1—1996.
Third edition 2003.

COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd
GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 5338 8

PREFACE

This Standard was prepared by the Standards Australia Committee BD-032, Composite Construction, to supersede AS 2327.1—1996 *Composite structures in structural steel and concrete*, Part 1—*Simply supported beams*.

This revision incorporates a number of technical and editorial changes. The principal differences are briefly outlined in the following:

- 1 *Shear connectors:*
 - (a) The value of the density reduction factor (k_r), used in the calculation of the design shear capacity (f_{ds}) of shear connectors with lightweight concrete, has been changed to equal 1.0 for welded-studs (since the effect of lower concrete density is already taken into account in the calculation of nominal shear capacity (f_{vs}) using Equation 8.3.2.1(2)), and a constant value of 0.8 for channels and high-strength structural bolts.
 - (b) A procedure for calculating the nominal shear capacity (f_{vs}) of channel or high-strength structural bolt shear connectors during the initial part of Construction Stage 5 when $15 \leq f'_{cj} < 20$ MPa, previously omitted from AS 2327.1, has been included, viz. at $f'_{cj} = 15$ MPa, f_{vs} equals 80% of the values given in Table 8.2 and Table 8.3 $f'_c = 20$ MPa, and linear interpolation is used for values of f'_{cj} between 15 and 20 MPa.
 - (c) The Grade 300, 100 PFC (parallel flange channel) may now be used as a fully equivalent shear connector to the Grade 250, 100 TFC (channel).
- 2 *Open-rib and closed-rib profiles* Distinction is made between open-rib and closed-rib profile steel sheeting when designing the shear connection of the composite beam.
- 3 *Welded stud locations* Clause 8.4.2 clarifies that when automatically welded studs are placed in the pans of sheeting ribs deemed to be perpendicular to the steel beam, no more than two studs are permitted between adjacent sheeting ribs. New rules have been written to allow shear connectors to be placed closer to steel ribs of closed-rib profiles.
- 4 *New reference material* New reference material has been provided for designers regarding the design of beams with large web penetrations and design for occupant-induced vibrations.
- 5 *Reinforcement* $f_{yr} = 500$. The maximum design yield strength has been increased to 500 MPa for the longitudinal shear reinforcement in the composite slab.

The terms 'normative' and 'informative' are used in this Standard to define the application of the appendix to which they apply. A 'normative' appendix is an integral part of a Standard, whereas an 'informative' appendix is only for information and guidance.

CONTENTS

	<i>Page</i>
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE.....	6
1.2 GENERAL.....	6
1.3 REFERENCED DOCUMENTS.....	9
1.4 DEFINITIONS.....	10
1.5 EXISTING STRUCTURES.....	16
1.6 DESIGN INFORMATION	16
1.7 CONSTRUCTION.....	17
1.8 NOTATION.....	17
SECTION 2 MATERIALS	
2.1 STEEL.....	25
2.2 CONCRETE AND REINFORCEMENT	25
2.3 MECHANICAL PROPERTIES.....	25
SECTION 3 GENERAL DESIGN REQUIREMENTS	
3.1 DESIGN	27
3.2 LOADS AND OTHER ACTIONS.....	28
3.3 DESIGN FOR LIMIT STATES.....	28
SECTION 4 ACTIONS AND DESIGN SITUATIONS	
4.1 GENERAL.....	30
4.2 CONSTRUCTION STAGES.....	30
SECTION 5 EFFECTIVE SECTION AND DESIGN ACTION EFFECTS FOR STRENGTH DESIGN	
5.1 GENERAL.....	32
5.2 EFFECTIVE SECTION OF A COMPOSITE BEAM CROSS-SECTION	32
5.3 CALCULATION OF DESIGN ACTION EFFECTS DUE TO DESIGN LOADS	37
SECTION 6 DESIGN FOR STRENGTH	
6.1 GENERAL.....	39
6.2 DESIGN	39
6.3 POTENTIALLY CRITICAL CROSS-SECTIONS	41
6.4 CALCULATION OF DESIGN VERTICAL SHEAR CAPACITY (ϕV_u) AND DESIGN MOMENT CAPACITY (ϕM_{bv}) AS A FUNCTION OF DEGREE OF SHEAR CONNECTION (β).....	42
6.5 CALCULATION OF MINIMUM DEGREE OF SHEAR CONNECTION β_i AT POTENTIALLY CRITICAL CROSS-SECTIONS	42
6.6 DISTRIBUTION OF SHEAR CONNECTORS BETWEEN POTENTIALLY CRITICAL CROSS-SECTIONS AND BEAM ENDS	43
SECTION 7 DESIGN FOR SERVICEABILITY	
7.1 GENERAL.....	45
7.2 DEFLECTION CONTROL.....	45
7.3 CRACK CONTROL	47
7.4 VIBRATION CONTROL	47

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
 - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-