



NSAI
Standards

SWiFT 6:2013

Timber in construction – Span tables and guidelines

SWiFT 6:2013

Incorporating amendments/corrigenda/National Annexes issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation - recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

<i>This document replaces:</i> I.S. 444:1998	<i>This document is based on:</i> SWiFT 6:2013 I.S. 444:1998	<i>Published:</i> 24 March, 2013 24 December, 1998
This document was published under the authority of the NSAI and comes into effect on: 24 March, 2013		ICS number: 79.080
NSAI 1 Swift Square, Northwood, Santry Dublin 9	T +353 1 807 3800 F +353 1 807 3838 E standards@nsai.ie W NSAI.ie	Sales: T +353 1 857 6730 F +353 1 857 6729 W standards.ie
Údarás um Chaighdeáin Náisiúnta na hÉireann		

Contents

Page

Foreword	3
1 Scope	4
2 Normative references	5
3 Terms and definitions	6
4 Symbols and abbreviated terms	7
4.1 Strength class	7
4.2 Span	7
4.3 Other abbreviations	7
4.4 Symbols	7
5 Timber properties	9
5.1 General	9
5.1.1 Timber marking	9
5.1.2 Timber durability	9
5.1.3 Grading and strength class	9
5.2 Other requirements	9
5.2.1 Fire	9
5.2.2 Environment	9
5.2.3 Vibration	9
6 Timber construction	10
6.1 Construction details	10
6.2 Notching and drilling	10
6.2.1 General	10
6.2.2 Notching	10
6.2.3 Drilling	10
6.2.4 Separation between notches and holes	10
6.3 Construction tolerances	10
6.4 Connections	10
6.5 Support of water cisterns	10
7 Design assumptions for span tables	11
7.1 General	11
7.2 Climatic action of the wind	11
7.3 Site location conditions	12
7.4 Fire resistance	13
7.5 Ground floors	13
7.6 Roof pitches	13
7.7 Overhang at eaves and gable	13
7.8 Gable ladders	13
7.9 Design criteria	13
7.9.1 Design loading	13
7.9.2 Categories of use	15
7.9.3 Design procedures	15
7.9.4 Lateral stability of joists	15
7.9.5 Lateral stability of rafters	16
7.9.6 Intermediate purlin support	16
7.9.7 Deflection	16
7.9.8 Member sizes	16
7.9.9 Purlins	16
7.9.10 Joints	16

SWiFT 6:2013

7.10	Rules for members not included in the maximum span tables	16
7.10.1	Tiling battens.....	16
7.10.2	Bridging and strutting	16
7.10.3	Wall plates on masonry walls.....	17
8	Finding the right table	18
9	Load-span tables	19
9.1	Floor span tables	19
9.2	Ceiling span tables	31
9.3	Flat roof span tables for SLC 1.....	33
9.4	Roof rafter span tables for SLC 1.....	37
9.5	Roof purlin span tables for SLC 1.....	45
9.6	Flat roof span tables for SLC 2.....	53
9.7	Roof rafter span tables for SLC 2.....	57
9.8	Roof purlin span tables for SLC 2.....	65
10	Wall studs	73
10.1	General.....	73
10.2	Design assumptions made for wall stud tables	74
10.3	Design assumptions made for particular wall stud arrangements	75
10.3.1	Single interior stud	75
10.3.2	Single end stud	75
10.3.3	Pair of interior studs.....	75
10.3.4	End pair of studs.....	75
Annex A	(informative) Figures	76
Annex B	(informative) Additional design guidance and clarification	84
B.1	General.....	84
B.2	Method for use of span tables for conditions other than SLC 1 or SLC 2.....	85
B.3	Further increase in maximum spans	86
B.4	Permanent loading assumptions	88
B.5	Vibration	89
B.6	Purlins.....	90
B.7	Calculation of maximum service load capacity of wall studs.....	90
B.7.1	General.....	90
B.7.2	Method of calculating the maximum service load capacity	91
B.7.3	Example of calculation for maximum service load capacity.....	92
Bibliography	94

Foreword

This SWiFT was developed by NSAI Timber Standards Consultative Committee, Working Group 2, Task Group 2 "Trussed rafters and timber in buildings".

The following participated in the development of this document:

- Mr. Aidan McMahon, Timber Consultant;
- Mr. Bob Davis, NSAI Agreement;
- Mr. Malcolm Jacob, Consulting Structural and Civil Engineer;
- Mr. Bill Robinson, Timber Design Services;
- Mr. Colin Short, Moran O'Connor Short;
- Mr. Conor Taaffe, HomeBond;
- Mr. John Wickham, Department of the Environment, Community and Local Government.

This document, which replaces I.S. 444:1998, relates to timber members commonly used in buildings constructed in Ireland and provides non-contradictory complementary information where those members are designed to I.S. EN 1995-1-1 and its National Annex.

The drawings in this document represent typical construction details. They are not prescriptive and alternative details may be appropriate. Attention is drawn to the acceptable constructional details published by the Department of the Environment, Community and Local Government which primarily show insulation and air tightness detailing.

During all construction related activities account should be taken of the Safety, Health and Welfare at Work (Construction) Regulations.

This publication does not purport to include all necessary provisions of a contract. Users are responsible for its correct application.

Compliance with this SWiFT does not of itself confer immunity from legal obligations.

In line with international standards the decimal point is shown as a comma (,) throughout this document.
--

SWiFT 6:2013

1 Scope

The span tables in this SWiFT give maximum spans for the following solid softwood structural members in buildings:

- Floor joists, including ground floor joists;
- Ceiling joists, including those supporting a standard water tank;
- Flat roof joists (0° to 5°);
- Rafters (20° to 45°); and
- Roof purlins.

Roof slopes other than those listed above are not included in this document.

Load tables for 44 mm x 100 mm timber wall studs are also included.

Maximum spans are given for members of a particular section size, spacing, strength class, and loading. For the tables, it has been assumed that the members are in service class 2 conditions (see I.S. EN 1995-1-1).

Structural members properly selected using these span tables comply with the structural design requirements of I.S. EN 1995-1-1 and its corresponding National Annex. It is intended that members so selected can be used in timber building construction without further design.

The loads on the members and the load combinations used for the preparation of the span tables comply with the requirements of the current editions of the following standards including their National Annexes:

- I.S. EN 1990;
- I.S. EN 1991-1-1;
- I.S. EN 1991-1-3; and
- I.S. EN 1991-1-4.

Using these loading standards, wind uplift becomes a major design criterion for members and their connections.

It is not feasible to provide span tables for all load cases and combinations. The loadings covered by the span tables in this document are set out in Table 1. Structural design of members subjected to loads or load combinations outside those covered by the span tables should be designed by appropriately qualified and experienced engineers in compliance with 1.3 (2) in I.S. EN 1990.

Flooring materials (e.g. T&G flooring boards, particle boards or plywood) are not covered.

Dormers and hipped roofs are complex constructions and should not be designed using this document. Instead their design should be referred to a competent timber designer; the load span tables should not be used in connection with these parts of a project.

The design and detailing of connections for all members are not included in this document and should be designed by appropriately qualified and experienced engineers in compliance with 1.3 (2) in I.S. EN 1990.

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
 - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-