

Irish Standard I.S. EN 12150-1:2015

Glass in building - Thermally toughened soda lime silicate safety glass - Part 1: Definition and description

© CEN 2015 No copying without NSAI permission except as permitted by copyright law.

I.S. EN 12150-1:2015

2015-10-12

Incorporating amendments/corrigenda/National Annexes issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard — national specification based on the consensus of an expert panel and subject to public consultation.

S.R.~xxx: Standard~Recommendation-recommendation~based~on~the~consensus~of~an~expert~panel~and~subject~to~public~consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

This document replaces/revises/consolidates the NSAI adoption of the document(s) indicated on the CEN/CENELEC cover/Foreword and the following National document(s):

NOTE: The date of any NSAI previous adoption may not match the date of its original CEN/CENELEC document.

Published:

This document is based on:

EN 12150-1:2015 2015-09-23

This document was published ICS number:

under the authority of the NSAI
and comes into effect on:
81.040.20

NOTE: If blank see CEN/CENELEC cover page

NSAI T +353 1 807 3800 Sales:

 1 Swift Square,
 F +353 1 807 3838
 T +353 1 857 6730

 Northwood, Santry
 E standards@nsai.ie
 F +353 1 857 6729

 Dublin 9
 W NSAI.ie
 W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

This is a free page sample. Access the full version online.

National Foreword

I.S. EN 12150-1:2015 is the adopted Irish version of the European Document EN 12150-1:2015, Glass in building - Thermally toughened soda lime silicate safety glass - Part 1: Definition and description

This document does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with this document does not of itself confer immunity from legal obligations.

In line with international standards practice the decimal point is shown as a comma (,) throughout this document.

This is a free page sample. Access the full version online.

This page is intentionally left blank

EUROPEAN STANDARD

EN 12150-1

NORME EUROPÉENNE

EUROPÄISCHE NORM

September 2015

ICS 81.040.20

Supersedes EN 12150-1:2000

English Version

Glass in building - Thermally toughened soda lime silicate safety glass - Part 1: Definition and description

Verre dans la construction - Verre de silicate sodocalcique de sécurité trempé thermiquement - Partie 1: Définition et description

Glas im Bauwesen - Thermisch vorgespanntes Kalknatron-Einscheiben-Sicherheitsglas - Teil 1: Definition und Beschreibung

This European Standard was approved by CEN on 8 August 2015.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

| 2 Normative references 6 3 Terms and definitions 6 4 Glass products 8 5 Fracture characteristics 8 6 Dimensions and tolerances 9 6.1 Nominal thickness and thickness tolerances 9 6.2.1 General 9 6.2.2 Width and length (sizes) 9 6.2.3 Meanium and minimum sizes 10 6.2.4 Edge deformation produced by the vertical process 11 6.3 Flatness 11 6.3.1 General 11 6.3.2 Measurement of overall bow 13 6.3.3 Measurement of overall bow 13 6.3.4 Measurement of verall bow 13 6.3.5 Measurement of edge lift (for horizontally toughened glass only) 15 6.3.5 Measurement of perimeter deformation of glass produced by air cushion toughening process 16 6.3.6 Measurement of local distortion (for vertically toughened glass only) 17 6.3.1 Limitation on overall bow, wave and perimeter deformation for toughened glass manufactured by air cushion process. | Contents | | |
|--|--------------|---|----|
| 1 Scope 6 2 Normative references 6 3 Terms and definitions 6 4 Glass products 8 5 Fracture characteristics 8 6 Dimensions and tolerances 9 6.1 Nominal thickness and thickness tolerances 9 6.2 Width and length (sizes) 9 6.2.1 General 9 6.2.2 Tolerances and squareness 10 6.2.3 Tolerances and squareness 10 6.2.4 Edge deformation produced by the vertical process 11 6.3.1 General 11 6.3.1 General 11 6.3.2 Measurement of overall bow 13 6.3.3 Measurement of edge lift (for horizontally toughened glass only) 15 6.3.4 Measurement of perimeter deformation of glass produced by air cushion toughening process 16 6.3.5 Measurement of local distortion (for vertically toughened glass only) 17 6.3.1 Limitation on overall bow, roller waves and edge lift f | Europ | ean foreword | 4 |
| 2 Normative references 6 3 Terms and definitions 6 4 Glass products 8 5 Fracture characteristics 8 6 Dimensions and tolerances 9 6.1 Nominal thickness and thickness tolerances 9 6.2 Width and length (sizes) 9 6.2.1 General 9 6.2.2 Maximum and minimum sizes 10 6.2.3 Tolerances and squareness 10 6.2.4 Edge deformation produced by the vertical process 11 6.3.1 Flatness 11 6.3.2 Measurement of overall bow 13 6.3.3 Measurement of wave and roller wave 14 6.3.4 Measurement of verall bow 15 6.3.5 Measurement of Perimeter deformation of glass produced by air cushion toughening process 16 6.3.5 Measurement of local distortion (for vertically toughened glass only) 17 6.3.1 Limitation on overall bow, roller waves and edge lift for horizontally toughened glass 18 6.3.2 Limitation on overall bow and local distortion for vertically toughened glass <th colspan="3">Introduction</th> | Introduction | | |
| 2 Normative references 6 3 Terms and definitions 6 4 Glass products 8 5 Fracture characteristics 8 6 Dimensions and tolerances 9 6.1 Nominal thickness and thickness tolerances 9 6.2 Width and length (sizes) 9 6.2.1 General 9 6.2.2 Maximum and minimum sizes 10 6.2.3 Tolerances and squareness 10 6.2.4 Edge deformation produced by the vertical process 11 6.3.1 Flatness 11 6.3.2 Measurement of overall bow 13 6.3.3 Measurement of wave and roller wave 14 6.3.4 Measurement of verall bow 15 6.3.5 Measurement of Perimeter deformation of glass produced by air cushion toughening process 16 6.3.5 Measurement of local distortion (for vertically toughened glass only) 17 6.3.1 Limitation on overall bow, roller waves and edge lift for horizontally toughened glass 18 6.3.2 Limitation on overall bow and local distortion for vertically toughened glass <th>1</th> <th>Scone</th> <th>6</th> | 1 | Scone | 6 |
| 3 Terms and definitions 6 4 Glass products 8 5 Fracture characteristics 8 6 Dimensions and tolerances 9 6.1 Nominal thickness and thickness tolerances 9 6.2 Width and length (sizes) 9 6.2.1 General 9 6.2.2 Maximum and minimum sizes 10 6.2.3 Tolerances and squareness 10 6.2.4 Edge deformation produced by the vertical process 11 6.3.1 General 11 6.3.2 Measurement of overall bow 13 6.3.3 Measurement of wave and roller wave 14 6.3.4 Measurement of wave and roller wave 14 6.3.5 Measurement of perimeter deformation of glass produced by air cushion toughening process 16 6.3.6 Measurement of local distortion (for vertically toughened glass only) 17 6.3.7 Limitation on overall bow, roller waves and edge lift for horizontally toughened glass 17 6.3.8 Limitation on overall bow and local distortion for vertically toughened glass 19 6.3.9 Limitation | _ | • | |
| 4 Glass products 8 5 Fracture characteristics 8 6 Dimensions and tolerances 9 6.1 Nominal thickness and thickness tolerances 9 6.2 Width and length (sizes) 9 6.2.1 General 9 6.2.2 Maximum and minimum sizes 10 6.2.3 Tolerances and squareness 10 6.2.4 Edge deformation produced by the vertical process 11 6.3.1 General 11 6.3.2 Hassurement of overall bow 13 6.3.3 Measurement of wave and roller wave 14 6.3.4 Measurement of wave and roller wave 14 6.3.5 Measurement of perimeter deformation of glass produced by air cushion toughening process 16 6.3.6 Measurement of local distortion (for vertically toughened glass only) 17 6.3.7 Limitation on overall bow, roller waves and edge lift for horizontally toughened glass manufactured by air cushion process 18 6.3.9 Limitation on overall bow and local distortion for vertically toughened glass 19 6.3.10 Other distortions 19 | _ | | |
| 5 Fracture characteristics | 3 | | |
| 6 Dimensions and tolerances 9 6.1 Nominal thickness and thickness tolerances 9 6.2 Width and length (sizes) 9 6.2.1 General 9 6.2.2 Maximum and minimum sizes 10 6.2.3 Tolerances and squareness 10 6.2.4 Edge deformation produced by the vertical process 11 6.3.1 Flatness 11 6.3.2 Measurement of overall bow 13 6.3.3 Measurement of wave and roller wave 14 6.3.4 Measurement of edge lift (for horizontally toughened glass only) 15 6.3.5 Measurement of local distortion (for vertically toughened glass only) 17 6.3.6 Measurement of local distortion (for vertically toughened glass only) 17 6.3.7 Limitation on overall bow, roller waves and edge lift for horizontally toughened glass 17 6.3.8 Measurement of local distortion (for vertically toughened glass only) 17 6.3.1 Limitation on overall bow, wave and perimeter deformation for toughened glass manufactured by air cushion process. 18 6.3.9 | 4 | Glass products | 8 |
| 6.1 Nominal thickness and thickness tolerances 9 6.2 Width and length (sizes) 9 6.2.1 General 9 6.2.2 Maximum and minimum sizes 10 6.2.3 Tolerances and squareness 10 6.2.4 Edge deformation produced by the vertical process 11 6.3.1 Flatness 11 6.3.2 Measurement of overall bow 13 6.3.3 Measurement of wave and roller wave 14 6.3.4 Measurement of edge lift (for horizontally toughened glass only) 15 6.3.5 Measurement of local distortion (for vertically toughened glass only) 17 6.3.6 Measurement of local distortion (for vertically toughened glass only) 17 6.3.7 Limitation on overall bow, roller waves and edge lift for horizontally toughened glass 17 6.3.8 Limitation on overall bow, wave and perimeter deformation for toughened glass 18 6.3.9 Limitation on overall bow and local distortion for vertically toughened glass 18 6.3.10 Other distortions 19 7 Edge and/or surface work, holes, notches and cut-outs 20 7.2 | 5 | Fracture characteristics | 8 |
| 6.2.1 Width and length (sizes) | 6 | | |
| 6.2.1 General 9 6.2.2 Maximum and minimum sizes 10 6.2.3 Tolerances and squareness 10 6.2.4 Edge deformation produced by the vertical process 11 6.3 Flatness 11 6.3.1 General 11 6.3.2 Measurement of overall bow 13 6.3.3 Measurement of wave and roller wave 14 6.3.4 Measurement of edge lift (for horizontally toughened glass only) 15 6.3.5 Measurement of perimeter deformation of glass produced by air cushion toughening process 16 6.3.6 Measurement of local distortion (for vertically toughened glass only) 17 6.3.7 Limitation on overall bow, roller waves and edge lift for horizontally toughened glass 17 6.3.8 Limitation on overall bow, wave and perimeter deformation for toughened glass manufactured by air cushion process 18 6.3.9 Limitation on overall bow and local distortion for vertically toughened glass 19 6.3.10 Other distortions 19 7 Edge and/or surface work, holes, notches and cut-outs 20 7.1 Warning 20 7.2 Edge working of glass for toughening 20 7.3 Profiled edges 21 7.4.1 General 21 7.4.2 Diameter of h | 6.1 | | |
| 6.2.2 Maximum and minimum sizes 10 6.2.3 Tolerances and squareness 10 6.2.4 Edge deformation produced by the vertical process 11 6.3 Flatness 11 6.3.1 General 11 6.3.2 Measurement of overall bow 13 6.3.3 Measurement of wave and roller wave 14 6.3.4 Measurement of edge lift (for horizontally toughened glass only) 15 6.3.5 Measurement of local distortion (for vertically toughened glass only) 17 6.3.6 Measurement of local distortion (for vertically toughened glass only) 17 6.3.7 Limitation on overall bow, roller waves and edge lift for horizontally toughened glass 17 6.3.8 Limitation on overall bow, wave and perimeter deformation for toughened glass manufactured by air cushion process 18 6.3.9 Limitation on overall bow and local distortion for vertically toughened glass 19 6.3.10 Other distortions 19 7 Edge and/or surface work, holes, notches and cut-outs 20 7.1 Warning 20 7.2 Edge working of glass for toughening 20 | 6.2 | | |
| 6.2.3 Tolerances and squareness | _ | | |
| 6.2.4 Edge deformation produced by the vertical process 11 6.3 Flatness 11 6.3.1 General 11 6.3.2 Measurement of overall bow 13 6.3.3 Measurement of wave and roller wave 14 6.3.4 Measurement of perimeter deformation of glass produced by air cushion toughening process 15 6.3.5 Measurement of local distortion (for vertically toughened glass only) 17 6.3.6 Measurement of local distortion (for vertically toughened glass only) 17 6.3.7 Limitation on overall bow, roller waves and edge lift for horizontally toughened glass 17 6.3.8 Limitation on overall bow, wave and perimeter deformation for toughened glass manufactured by air cushion process 18 6.3.9 Limitation on overall bow and local distortion for vertically toughened glass 19 6.3.10 Other distortions 19 7 Edge and/or surface work, holes, notches and cut-outs 20 7.1 Warning 20 7.2 Edge working of glass for toughening 20 7.3 Profiled edges 21 7.4.1 General 21 7.4.2 </td <td>_</td> <td></td> <td></td> | _ | | |
| 6.3 Flatness 11 6.3.1 General 12 6.3.2 Measurement of overall bow 13 6.3.3 Measurement of wave and roller wave 14 6.3.4 Measurement of perimeter deformation of glass produced by air cushion toughening process 15 6.3.5 Measurement of local distortion (for vertically toughened glass only) 17 6.3.6 Measurement of local distortion (for vertically toughened glass only) 17 6.3.7 Limitation on overall bow, roller waves and edge lift for horizontally toughened glass 17 6.3.8 Limitation on overall bow, wave and perimeter deformation for toughened glass 18 6.3.9 Limitation on overall bow and local distortion for vertically toughened glass 19 6.3.10 Other distortions 19 7 Edge and/or surface work, holes, notches and cut-outs 20 7.1 Warning 20 7.2 Edge working of glass for toughening 20 7.3 Profiled edges 21 7.4.1 General 21 7.4.2 Diameter of holes 21 7.4.3 Limitations on position of holes 21 <td>_</td> <td></td> <td></td> | _ | | |
| 6.3.1 General 11 6.3.2 Measurement of overall bow 13 6.3.3 Measurement of wave and roller wave 14 6.3.4 Measurement of edge lift (for horizontally toughened glass only) 15 6.3.5 Measurement of perimeter deformation of glass produced by air cushion toughening process 16 6.3.6 Measurement of local distortion (for vertically toughened glass only) 17 6.3.7 Limitation on overall bow, roller waves and edge lift for horizontally toughened glass 17 6.3.8 Limitation on overall bow, wave and perimeter deformation for toughened glass manufactured by air cushion process 18 6.3.9 Limitation on overall bow and local distortion for vertically toughened glass 19 6.3.10 Other distortions 19 7 Edge and/or surface work, holes, notches and cut-outs 20 7.1 Warning 20 7.2 Edge working of glass for toughening 20 7.3 Profiled edges 21 7.4 Round holes 21 7.4.1 General 21 7.4.2 Diameter of holes 21 7.4.3 Limitations on position of holes 21 7.4.4 Tolerances on hole diameters 22 7.5 Holes/others 23 7.6 Notches and cut-outs 24 | _ | | |
| 6.3.2 Measurement of overall bow 13 6.3.3 Measurement of wave and roller wave 14 6.3.4 Measurement of perimeter deformation of glass produced by air cushion toughening process 16 6.3.5 Measurement of perimeter deformation of glass produced by air cushion toughening process 16 6.3.6 Measurement of local distortion (for vertically toughened glass only) 17 6.3.7 Limitation on overall bow, roller waves and edge lift for horizontally toughened glass manufactured by air cushion process 18 6.3.8 Limitation on overall bow and local distortion for vertically toughened glass 19 6.3.9 Limitation on overall bow and local distortion for vertically toughened glass 19 6.3.10 Other distortions 19 7 Edge and/or surface work, holes, notches and cut-outs 20 7.1 Warning 20 7.2 Edge working of glass for toughening 20 7.3 Profiled edges 21 7.4.1 General 21 7.4.2 Diameter of holes 21 7.4.3 Limitations on position of holes 21 7.4.5 Tolerances on position of holes 23 | | | |
| 6.3.3 Measurement of wave and roller wave 14 6.3.4 Measurement of edge lift (for horizontally toughened glass only) 15 6.3.5 Measurement of perimeter deformation of glass produced by air cushion toughening process 16 6.3.6 Measurement of local distortion (for vertically toughened glass only) 17 6.3.7 Limitation on overall bow, roller waves and edge lift for horizontally toughened glass 17 6.3.8 Limitation on overall bow, wave and perimeter deformation for toughened glass 18 6.3.9 Limitation on overall bow and local distortion for vertically toughened glass 19 6.3.10 Other distortions 19 7 Edge and/or surface work, holes, notches and cut-outs 20 7.1 Warning 20 7.2 Edge working of glass for toughening 20 7.3 Profiled edges 21 7.4.1 General 21 7.4.2 Diameter of holes 21 7.4.3 Limitations on position of holes 21 7.4.4 Tolerances on hole diameters 22 7.5 Holes/others 23 7.6 Notches and cut-outs | | | |
| 6.3.4 Measurement of edge lift (for horizontally toughened glass only) 15 6.3.5 Measurement of perimeter deformation of glass produced by air cushion toughening process 16 6.3.6 Measurement of local distortion (for vertically toughened glass only) 17 6.3.7 Limitation on overall bow, roller waves and edge lift for horizontally toughened glass 17 6.3.8 Limitation on overall bow, wave and perimeter deformation for toughened glass manufactured by air cushion process 18 6.3.9 Limitation on overall bow and local distortion for vertically toughened glass 19 6.3.10 Other distortions 19 7 Edge and/or surface work, holes, notches and cut-outs 20 7.1 Warning 20 7.2 Edge working of glass for toughening 20 7.3 Profiled edges 21 7.4.1 General 21 7.4.2 Diameter of holes 21 7.4.3 Limitations on position of holes 21 7.4.5 Tolerances on hole diameters 22 7.5 Holes/others 23 7.6 Notches and cut-outs 24 7.7 Shaped pane | | | |
| 6.3.5Measurement of perimeter deformation of glass produced by air cushion toughening process166.3.6Measurement of local distortion (for vertically toughened glass only)176.3.7Limitation on overall bow, roller waves and edge lift for horizontally toughened glass176.3.8Limitation on overall bow, wave and perimeter deformation for toughened glass186.3.9Limitation on overall bow and local distortion for vertically toughened glass196.3.10Other distortions197Edge and/or surface work, holes, notches and cut-outs207.1Warning207.2Edge working of glass for toughening207.3Profiled edges217.4Round holes217.4.1General217.4.2Diameter of holes217.4.3Limitations on position of holes217.4.4Tolerances on hole diameters227.5Tolerances on position of holes237.5Holes/others237.6Notches and cut-outs247.7Shaped panes24 | | | |
| 16 6.3.6 Measurement of local distortion (for vertically toughened glass only) 17 6.3.7 Limitation on overall bow, roller waves and edge lift for horizontally toughened glass 17 6.3.8 Limitation on overall bow, wave and perimeter deformation for toughened glass 18 6.3.9 Limitation on overall bow and local distortion for vertically toughened glass 19 6.3.10 Other distortions 19 7 Edge and/or surface work, holes, notches and cut-outs 20 7.1 Warning 20 7.2 Edge working of glass for toughening 20 7.3 Profiled edges 21 7.4 Round holes 21 7.4.1 General 21 7.4.2 Diameter of holes 21 7.4.3 Limitations on position of holes 21 7.4.4 Tolerances on hole diameters 22 7.4.5 Tolerances on position of holes 23 7.5 Holes/others 23 7.6 Notches and cut-outs 24 7.7 Shaped panes 24 | | | |
| 6.3.6Measurement of local distortion (for vertically toughened glass only)176.3.7Limitation on overall bow, roller waves and edge lift for horizontally toughened glass176.3.8Limitation on overall bow, wave and perimeter deformation for toughened glass manufactured by air cushion process186.3.9Limitation on overall bow and local distortion for vertically toughened glass196.3.10Other distortions197Edge and/or surface work, holes, notches and cut-outs207.1Warning207.2Edge working of glass for toughening207.3Profiled edges217.4Round holes217.4.1General217.4.2Diameter of holes217.4.3Limitations on position of holes217.4.4Tolerances on hole diameters227.5Holes/others237.6Notches and cut-outs247.7Shaped panes24 | 6.3.5 | | |
| 6.3.7Limitation on overall bow, roller waves and edge lift for horizontally toughened glass | | | |
| glass | | | 17 |
| 6.3.8Limitation on overall bow, wave and perimeter deformation for toughened glass manufactured by air cushion process | 6.3.7 | | |
| manufactured by air cushion process | | glass | 17 |
| 6.3.9 Limitation on overall bow and local distortion for vertically toughened glass. 19 6.3.10 Other distortions. 19 7 Edge and/or surface work, holes, notches and cut-outs. 20 7.1 Warning. 20 7.2 Edge working of glass for toughening. 20 7.3 Profiled edges. 21 7.4 Round holes. 21 7.4.1 General. 21 7.4.2 Diameter of holes. 21 7.4.3 Limitations on position of holes. 21 7.4.4 Tolerances on hole diameters. 22 7.4.5 Tolerances on position of holes. 23 7.5 Holes/others. 23 7.6 Notches and cut-outs. 24 7.7 Shaped panes. 24 | 6.3.8 | | |
| 6.3.10 Other distortions 19 7 Edge and/or surface work, holes, notches and cut-outs 20 7.1 Warning 20 7.2 Edge working of glass for toughening 20 7.3 Profiled edges 21 7.4 Round holes 21 7.4.1 General 21 7.4.2 Diameter of holes 21 7.4.3 Limitations on position of holes 21 7.4.4 Tolerances on hole diameters 22 7.4.5 Tolerances on position of holes 23 7.5 Holes/others 23 7.6 Notches and cut-outs 24 7.7 Shaped panes 24 | | | |
| 7 Edge and/or surface work, holes, notches and cut-outs 20 7.1 Warning 20 7.2 Edge working of glass for toughening 20 7.3 Profiled edges 21 7.4 Round holes 21 7.4.1 General 21 7.4.2 Diameter of holes 21 7.4.3 Limitations on position of holes 21 7.4.4 Tolerances on hole diameters 22 7.4.5 Tolerances on position of holes 23 7.5 Holes/others 23 7.6 Notches and cut-outs 24 7.7 Shaped panes 24 | | | |
| 7.1 Warning 20 7.2 Edge working of glass for toughening 20 7.3 Profiled edges 21 7.4 Round holes 21 7.4.1 General 21 7.4.2 Diameter of holes 21 7.4.3 Limitations on position of holes 21 7.4.4 Tolerances on hole diameters 22 7.4.5 Tolerances on position of holes 23 7.5 Holes/others 23 7.6 Notches and cut-outs 24 7.7 Shaped panes 24 | 6.3.10 | | |
| 7.2 Edge working of glass for toughening 20 7.3 Profiled edges 21 7.4 Round holes 21 7.4.1 General 21 7.4.2 Diameter of holes 21 7.4.3 Limitations on position of holes 21 7.4.4 Tolerances on hole diameters 22 7.4.5 Tolerances on position of holes 23 7.5 Holes/others 23 7.6 Notches and cut-outs 24 7.7 Shaped panes 24 | 7 | Edge and/or surface work, holes, notches and cut-outs | 20 |
| 7.3 Profiled edges 21 7.4 Round holes 21 7.4.1 General 21 7.4.2 Diameter of holes 21 7.4.3 Limitations on position of holes 21 7.4.4 Tolerances on hole diameters 22 7.4.5 Tolerances on position of holes 23 7.5 Holes/others 23 7.6 Notches and cut-outs 24 7.7 Shaped panes 24 | | | |
| 7.4 Round holes 21 7.4.1 General 21 7.4.2 Diameter of holes 21 7.4.3 Limitations on position of holes 21 7.4.4 Tolerances on hole diameters 22 7.4.5 Tolerances on position of holes 23 7.5 Holes/others 23 7.6 Notches and cut-outs 24 7.7 Shaped panes 24 | 7.2 | | |
| 7.4.1 General 21 7.4.2 Diameter of holes 21 7.4.3 Limitations on position of holes 21 7.4.4 Tolerances on hole diameters 22 7.4.5 Tolerances on position of holes 23 7.5 Holes/others 23 7.6 Notches and cut-outs 24 7.7 Shaped panes 24 | 7.3 | | |
| 7.4.2 Diameter of holes 21 7.4.3 Limitations on position of holes 21 7.4.4 Tolerances on hole diameters 22 7.4.5 Tolerances on position of holes 23 7.5 Holes/others 23 7.6 Notches and cut-outs 24 7.7 Shaped panes 24 | | | |
| 7.4.3 Limitations on position of holes 21 7.4.4 Tolerances on hole diameters 22 7.4.5 Tolerances on position of holes 23 7.5 Holes/others 23 7.6 Notches and cut-outs 24 7.7 Shaped panes 24 | | | |
| 7.4.4 Tolerances on hole diameters227.4.5 Tolerances on position of holes237.5 Holes/others237.6 Notches and cut-outs247.7 Shaped panes24 | | | |
| 7.4.5 Tolerances on position of holes | 7.4.3 | | |
| 7.5 Holes/others | | | |
| 7.6 Notches and cut-outs | 7.4.5 | | |
| 7.7 Shaped panes24 | 7.5 | | |
| The state of the s | 7.6 | | |
| 8 Fragmentation test 24 | 7.7 | Shaped panes | 24 |
| o i i uginentutivii test | 8 | Fragmentation test | 24 |

| 8.1 | General | 24 |
|------------|---|----|
| 8.2 | Dimensions and number of test specimens | 24 |
| 8.3 | Test procedure | 24 |
| 8.4 | Assessment of fragmentation | |
| 8.5 | Minimum values from the particle count | 26 |
| 8.6 | Selection of the longest particle | |
| 8.7 | Maximum length of longest particle | 27 |
| 9 | Other physical characteristics | 27 |
| 9.1 | Optical distortion | 27 |
| 9.1.1 | Thermally toughened soda lime silicate safety glass produced by vertical toughening | 27 |
| 9.1.2 | Thermally toughened soda lime silicate safety glass produced by horizontal | |
| | toughening | 27 |
| 9.2 | Anisotropy (iridescence) | |
| 9.3 | Thermal durability | |
| 9.4 | Mechanical strength | |
| 9.5 | Classification of performance under accidental human impact | 28 |
| 10 | Marking | 28 |
| Annex | A (informative) Curved thermally toughened soda lime silicate safety glass | 30 |
| Annex | B (informative) Alternative method for the measurement of roller wave distortion | 31 |
| B.1 | Apparatus | 31 |
| B.2 | Method | 31 |
| B.3 | Limitations | 32 |
| B.4 | Alternative use of apparatus | 32 |
| Annex | C (informative) Examples of particle count | 33 |
| Annex | D (informative) Risk of spontaneous breakage of toughened glass due to nickel | |
| | sulfide inclusion | 36 |
| Biblio | graphy | 37 |
| • | | |

European foreword

This document (EN 12150-1:2015) has been prepared by Technical Committee CEN/TC 129 "Glass in building", the secretariat of which is held by NBN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by March 2016, and conflicting national standards shall be withdrawn at the latest by March 2016.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 12150-1:2000.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

EN 12150, *Glass in building* — *Thermally toughened soda lime silicate safety glass*, consists of the following parts:

- Part 1: Definitions and description;
- Part 2: Evaluation of conformity/Product standard.

This European Standard differs from EN 12150-1:2000 as follows:

- a) some figures have been revised and some new figures have been added;
- b) new terms and definitions have been included in Clause 3, e.g. air cushion process (3.6), edge lift (3.9) and roller wave distortion (3.13);
- c) further nominal thicknesses have been included in Table 1;
- d) Subclause 6.2.3 "Tolerances and squareness" has been completely revised; the squareness of rectangular glass panes is now expressed by the difference between its diagonals;
- e) Clauses 6 and 7 have been completely revised (including the air cushion manufacturing process);
- f) the normative annex "Determination of U value" has been deleted;
- g) a new informative annex dealing with an alternative method for the measurement of roller wave distortion has been added.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

Thermally toughened soda lime silicate safety glass has a safer breakage behaviour when compared with annealed glass. When it should be used to offer protection under accidental human impact, thermally toughened soda lime silicate safety glass also should be classified according to EN 12600.

NOTE CEN/TC 129/WG 8 is producing standards for the determination of the design strength of glass and is preparing a design method.

1 Scope

This European Standard specifies tolerances, flatness, edgework, fragmentation and physical and mechanical characteristics of monolithic flat thermally toughened soda lime silicate safety glass for use in buildings.

Information on curved thermally toughened soda lime silicate safety glass is given in Annex A, but this product does not form part of this European Standard.

Other requirements, not specified in this European Standard, can apply to thermally toughened soda lime silicate safety glass which is incorporated into assemblies, e.g. laminated glass or insulating glass units, or undergo an additional treatment, e.g. coating. The additional requirements are specified in the appropriate glass product standard. Thermally toughened soda lime silicate safety glass, in this case, does not lose its bending strength characteristics and its resistance to temperature differentials.

Surface finished glasses (e.g. sandblasted, acid etched) after toughening are not covered by this European Standard.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 572-1, Glass in building — Basic soda lime silicate glass products — Part 1: Definitions and general physical and mechanical properties

EN 572-2, Glass in building — Basic soda lime silicate glass products —Part 2: Float glass

EN 572-4, Glass in building — Basic soda lime silicate glass products — Part 4: Drawn sheet glass

EN 572-5, Glass in building — Basic soda lime silicate glass products — Part 5: Patterned glass

EN 572-8, Glass in building — Basic soda lime silicate glass products — Part 8: Supplied and final cut sizes

EN 1096-1, Glass in building — Coated glass - Part 1: Definitions and classification

EN 1288-3, Glass in building — Determination of the bending strength of glass — Part 3: Test with specimen supported at two points (four point bending)

EN 14428, Shower enclosures — Functional requirements and test methods

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

thermally toughened soda lime silicate safety glass thermally toughened safety glass

glass within which a permanent surface compressive stress, additionally to the basic mechanical strength, has been induced by a controlled heating and cooling process in order to give it greatly increased resistance to mechanical and thermal stress and prescribed fragmentation characteristics



| This is a free preview | Purchase the entire | e publication at the link below: |
|------------------------|---|----------------------------------|
|------------------------|---|----------------------------------|

Product Page

- Dooking for additional Standards? Visit Intertek Inform Infostore
- Dearn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation